



**Standocryl® Clear PFC 20**  
**Superior appearance and performance.**



**The Art of Refinishing.**

# Standocryl® Clear PFC 20

## 2.1 Clear to meet the most stringent VOC regulations.

- Ideal for all types of jobs—from spot repairs to multi-panel repairs
- Excellent gloss and finish help ensure customer satisfaction
- Ease of application, buffing and polishing improve results
- Fast drying and harder out of bake for increased productivity
- Can be sprayed in a 1.5 continuous application process or in 2 coats, offering versatility



**Standocryl® ProFuture Clear (PFC) 20 is next-generation technology for professional refinishers. It is a productive clear specifically designed to deliver a superior appearance over Standox® solventborne and waterborne basecoats. This 2.1 clear is VOC compliant.**

### **Easy to spray. Superior performance.**

Standocryl® Clear PFC 20 offers the convenience of a 1.5 continuous application process, but is versatile enough to allow refinishers to use a 2-coat application process if desired. This high-productivity clearcoat also gives refinishers the ability to sand and polish after a 20-minute bake and cool-down. And, bumpers can be installed just 30 minutes after the bake cycle.

From spot repairs to multi-panel repairs, Standocryl® Clear PFC 20 is easy to spray and delivers excellent gloss and finish.

### **Fast drying. Saves energy. Increases productivity.**

With its fast drying times, Standocryl® Clear PFC 20 not only saves energy, it helps increase productivity. Simply bake for 20 minutes at 130°F (55°C) panel temperature or air dry for 8 hours to overnight at 68°F (20°C).

### **Fast facts**

Code: 020 16211

Mix Ratio: 2:1 + 15% PF Thinner

Standox® Hardeners:

PFH 15-25 (020 16212)

PFH 25-30 (020 16213)

PFH 30-35 (020 16214)

Standox® Thinner:

PF Thinner (020 16215)

Compliance: 2.1 lbs/gal (250 g/L)

Standox • 47802 West Anchor Court • Plymouth, Michigan 48170 • USA • standoxna.com